

AMENDMENTS TO THE CLAIMS:

Please replace the current claim list with the following updated claim list:

1. (Currently Amended) A cable wiring construction for a cable provided between a controller operated by a seater on a seat and a unit body[']
comprising:

[wherein] a locking portion for locking an intermediate portion of said cable is provided on a seat back of said seat;[, and]

a height position of said cable in said locking portion [is] being set so as to be higher than a seat cushion of said seat; and

said cable having first and second ends, said first end being connected to a controller and said second end being connected to a mechanism for controlling the position of said seat, and said cable being disposed exterior to said seat.

2. (Currently Amended) The cable wiring construction according to claim 1,
[wherein] further comprising:

a string-form locking member [is] being provided between said seat back and a backboard fixed to said seat back with a plurality of clips[.];

said locking member is provided with at least a pair of locked portions that are locked by clips at different places;

and said locking portion ~~which is positioned by being held by said back~~
and said backboard, said locking portion being located ~~and exits in an~~
~~elongated form~~ on an outer periphery of said backboard ~~is provided between~~
both of said locked portions.

3. (New) A wiring arrangement comprising:

a seat, said seat having a seat back and a cushion;

a hand held controller;

a seat positioning mechanism located below the seat;

a first elongated member connecting the hand held controller to the seat
positioning mechanism, said first elongated mechanism having an intermediate
portion;

a second elongated member having first and second ends respectively
fixed to first and second locations on said seat back, said second elongated
member being exterior to said seat back and having an intermediate portion
connected to said intermediate portion of said first elongated member; and

said intermediate portion of said second elongated member being located
on an outer periphery of said seat back so that said intermediate portion of said
first elongated mechanism is higher than said seat cushion.

4. (New) The wiring arrangement of claim 3 wherein said first elongated member is a cable.
5. (New) The wiring arrangement of claim 3 wherein said second elongated member is a cable.
6. (New) The wiring arrangement of claim 3 further comprising clips for locking said first and second ends of said second elongated member to said seat.
7. (New) The wiring arrangement of claim 5 wherein said intermediate portion of said cable is a loop or knot.